

Toroidal Amplifers

TK Systems - The perfect blend of reliablity, performance & affordability.



Applications

- Tour Sound
- Live Sound

Products in the Series

- TK 9000
- TK 6000
- TK 5000
- TK 4000
- TK 3000

Features

- High power amplification for touring, commercial & residential application
- · Built-in High-Pass filter with selectable frequency cut-off.
- Efficient cooling system with multi-step heat protection.
- Selectable gain plus scalable voltage Peak limiter to allow custom configuration as per application requirements
- · Individual gain control

TK Series continues our Amplification legacy of unmatched sonic accuracy, putting tonal balance at the peak - Delivers between 500 & 7000 Watts of Power - Rugged build quality assures resistance against decades of use on the tour

British Acoustics
Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com



TK-9000

2 Channel, Audio Power Amplifier for Touring

Technical Specifications

Rated Power Per Channel (8Ω)	1400 Watts RMS Stereo
Rated Power Per Channel (4Ω)	2200 Watts RMS Stereo
Bridge Mode (8Ω)	3500 Watts RMS Stereo
Bridge Mode (4Ω)	7040 Watts RMS Stereo
Number of Channels	2 Channels
Controls	Sensitivity Selection, High Pass Cut Off,
	Stereo, Bridge, Parallel Switch
Dampning Factor	> 350 at 8ohms
Signal to Noise Ratio (1 kHz, 8	- 100 dB
Ohms)	
THD	< 0.02% THD / 4ohms and 8 ohms



Enclosure	Tour Grade Rugged Aluminum Chasis
Finish	Metallic Matte Finish - Ivory White
Knobs	Controlled Increment ABS Knobs
Mounting System	19" Standard Rack Mount Ears
Height	5.25" (3 RU)
Width	19"
Depth	18.2"
Weight	32.5 Kgs







British Acoustics

Creative Park, Langley Park,

T: +44 191 373 7638

E: info@britishacoustics.com

All Rights Reserved - British Acoustics