


ALPHA BLU 415

15" BLU-SERIES PERFORMANCE INSTALLATION SPEAKER



 **BA**
BRITISH ACOUSTICS



ACOUSTICAL SPECIFICATIONS

- Freq. Response (-3 dB) : 55 Hz - 20 kHz
- Freq. Range (-10 dB) : 40 Hz - 20 kHz
- Rated Power : 600W, 2400W Peak
- H Dispersion : 90° (-6 dB)
- V Dispersion : 50° (-6 dB)
- User Rotatable Horns
- Crossover : .2 kHz or Bi-amplified
- Nominal Impedance : 8 Ω
- Max Output: Cont 128 dB, Peak 134 dB
- 2 x Speak-On Sockets, Input & Thru

SYSTEM SPECIFICATIONS

- Recommended Subwoofers : See Systems Chart for compatible subwoofers
- Recommended System Control : Delta Drive DSP Control Systems
- Recommended Amplifiers : See Amplifier load calculation chart

LF TRANSDUCER

- 15" Low Frequency Driver
- 550W, 2200W Peak
- 3" Copper Voice Coil - Ferrite Magnet

- Enhanced Airflow Path for minimal power
- Aluminum Demodulation Ring for reduced distortion

HF TRANSDUCER

- 1.4" Exit HF Compression Driver
- 50W, 200W Peak
- 2.5" Voice Coil - Ferrite Magnet
- Alpha Contour Waveguide ensuring consistent coverage

HOUSING

- Marine Birchply Enclosure
- Granular Scratch Free Polyurea Paint
- Perforated Black, Pressed Steel Grills
- Integrated Handles on Either Side
- Includes a set of round bottom feet for secure and stable stacking
- Sloped Input Plates
- M10 Flying inserts
- Installation brackets : Alpha Throne (H), Alpha Throne (V), Alpha Yoke B410

AESTHETIC SPECIFICATIONS

- British Acoustics Signature Umber Brown

Tone

- Blue Decals on Grills for better Aesthetics
- Available in a RAL code of your choice (24 nos, minimum)

IP SPECIFICATIONS

- Standard Version : IP 42 - Offers basic protection against dust & splashes

OPERATING PARAMETERS

- Operating positions: Can be deployed horizontally or vertically with the correct installation brackets or can be used as a monitor
- Maximum permitted ambient temperature (Ta max) 55° C (124° F)
- Minimum permitted ambient temperature (Ta min): -20° C (-4° F)

OPTIONAL ACCESSORIES

- See system chart for the System Accessories

SIZE

- Product: 685 x 444 x 368 mm (H x W x D)
- Product: 27 x 17.5 x 14.5 inch (H x W x D)
- Packed individually

WEIGHT

- Net : 24.19 Kgs
- Net : 53.3 Lbs


SHIPPING INFORMATION

- Carton Size
760 x 519 x 443 mm (H x W x D)
29.9 x 20.4 x 17.4 inch (H x W x D)
- Gross Weight : 25.3 Kgs / 55.78 Lbs
- Packed : Individually

PRODUCT INFORMATION

- Model No : Alpha Blu 415
- Series 4
- Tags : 15" Blu-Series Performance Installation Speaker

BA & British Acoustics are registered trademarks in the UK and other regions worldwide.
Safe Installation & Rigging Practices : Installation must be by authorized personnel, following safety and rigging standards to avoid liability.
*Product specifications and design may change due to raw material variations or the addition of new features and technologies for improved performance and reliability.
*SPL Calculated @ 1m, Free Field with Pink Noise - Crest Factor 4





One Basecamp, 49 Jamaica Street, Liverpool, L10AH, Great Britain.
Email - info@britishacoustics.com | Tel - +44 (0) 151 515 0170
www.britishacoustics.com