

9 Series

Delta 900 - For the stage that accepts no compromise



Applications

- Portable sound reinforcement
- · Live sound reinforcement
- · Unobtrusive stage monitoring
- Corporate AV events and conferences
- Mobile Touring
- Speech Transmission

Features

- Custom British Acoustics Transducers
- · Preset Library available
- · Pole mount socket available (except the Delta 925)
- True full-range performance
- · Durable construction with scratch resistant textured pain finish
- · Ideal for floor monitoring, side-fills or FOH use

Products in the Series

- Delta 925
- Delta 915
- Delta 912

Delta 900 Live sound systems are a range of premium portable speakers that deliver superior sound quality, power handling, and craftsamnship in their class. Extreme quality control, skilled craftsmanship and a systems design approach has led to the groudbreaking success of the Delta 900 series



Technical Specifications

Frequency Range (+/- 10dB)	34 Hz-20 kHz
Frequency Response (+/- 3dB)	42 Hz-19 kHz
Dispersion (- 6dB)	90 x 50
Max Spl	136 dB SPL Peak
Connection	2x Speakon Connectors
Rated Power	1600W Continuous, 6400W Peak
Nominal Impedance	4 Ohms
LF Driver	2 x 15" Low Frequency Driver
HF Driver	1.4" Exit Compression Driver



Enclosure	Marine Birchwood Cabinet, Premium Grade
Grill	Powder coated durable grill with acoustically
	Transparent foam
Finish	British Acoustics' Signature Brown Finish
Mounting System	Integrated Handles - M-10 insertion points
Height	42"
Width	22.4"
Depth	22.4"
Weight	51 Kgs







British Acoustics Creative Park, Langley Park, Durham DH7 9TT, UK. All Rights Reserved - British Acoustics

M: +44 (0) 1494 535 312 E: info@britishacoustics.com