

# 1 Series

## VA Systems - VA Versatile Application Systems



### Applications

- Fixed Installations
- Cafes, Bars & Restaurants
- Retail Outlets
- Corporate AV
- Hotels & Convention Centres
- Educational Offices

### Features

- IPX-66 rated for environmental applications
- Integrated 70V transformer with a 8 ohms bypass
- Pendant, Wall or Landscape modes
- IPX-66 rated ABS enclosure
- Co-herent phase response from a co-axial design

### Products in the Series

- VA 116 XTW
- VA 114 XTW

The VA indoor/outdoor multi-purpose speaker systems feature a 2-way coaxial design complete with a 6.5" or 4" woofer and 1" tweeter. The IP66 weather resistant ABS plastic construction is able to withstand outdoor environments while remaining aesthetically pleasing for indoor use. The VA systems can be used for both commercial and residential applications.

# VA 114 XTW

## 4" Versatile Application Speaker

### Technical Specifications

<b>Frequency Range</b> (+/- 10dB)	121 Hz - 20 kHz
<b>Frequency Response</b> (+/- 3dB)	129 Hz - 20 kHz
<b>Coverage Pattern</b>	100° x 100°
<b>Max Spl</b>	115 dB
<b>LF Driver</b>	4" Weather Resistant Coaxial Driver
<b>HF Driver</b>	1" Dome Compression Drivers, 1.4" VC
<b>Rated Power</b>	20W Continuous, 80W Peak
<b>Transformer Taps</b>	20W, 10W, 5W - 100 / 70 V
<b>Nominal Impedance</b>	8 Ohms or 100/70 V
<b>Sensitivity</b>	95 dB

### General Specifications

<b>Enclosure</b>	IPX 66 rated ABS Enclosure
<b>Grill</b>	Powder Coated rust-free grill
<b>Finish</b>	Sesimic Black Finish
<b>Mounting System</b>	Wall, Floor or Pendant Mounting Installation Kits
<b>Height</b>	11.2"
<b>Width</b>	7"
<b>Depth</b>	6.3"
<b>Weight</b>	2.5 Kgs

