

1 Series

VS Systems - VS Installation Systems



Applications

- Fixed Installations
- Cafes, Bars & Restaurants
- Retail Outlets
- Corporate AV
- Hotels & Convention Centres
- Educational Offices

Features

- Full range surface-mount loudspeaker for indoor and outdoor installation applications
- 8 Ohm direct input for low impedance applications
- Boxed with a yoke bracket for quick & accurate installation
- Ported enclosure for better low frequency response.
- Spring Terminal inputs for easy termination

Products in the Series

- VS 108T
- VS 106T
- VS 104T

The VS series is perhaps the most versatile range of our loudspeakers. With 4-inch & 8-inch options, the VS series ably complements all indoor venues for foreground/background sound reinforcement. The low s

British Acoustics

Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com

www.britishacoustics.com

VS 106T

6" two-way installation speakers

Technical Specifications

Frequency Range (-10dB)	80 Hz - 16 kHz
Frequency Response (-3dB)	72 Hz - 20 kHz
Coverage Pattern	100° x 100°
Max Spl	110 dB
LF Driver	6" Extended LF Driver, 2" VC - Ferrite
HF Driver	1" Silk Dome Compression Drivers, 1.4" VC
Rated Power	60W Continuous, 240W Peak
Nominal Impedance	8 Ohms or 100/70 V
Transformer Taps	40W, 20W, 10W - 100 / 70 V
Sensitivity	88 dB

General Specifications

Enclosure	Dura-light ABS Enclosure
Grill	Black Powder-coated durable grill
Finish	Sesimic Black Finish
Mounting System	Installation Yoke
Height	11.2"
Width	7.8"
Depth	7.6"
Weight	4.2 Kgs

