

Delta Control

Speaker Management & Signal Processing Units.

**NEW
RELEASE!**



Applications

- Fixed Instalations
- Touring Instalations

Features

- Excellent sonic performance with 24bit high end converters coupled with 96kHz sample rate
- Upto 4 inputs, 8 outputs with full matrix mixing.
- 30 band parametric equalization per input channel
- 7 band parametric equalization per output channel
- Each band can be switched to Bell, Shelving, LP/HP, All-Pass, Band-Pass and Notch

Products in the Series

- Delta Drive 26X
- Delta Drive 48X
- Delta Drive 28X

The Delta Control Speaker Management Systems feature three models; Delta 26 (2-in 6-out), Delta 28 (2-in 8-out) & Delta 48 (4-in 8-out). The systems can be controlled using the Delta Control Software for a brief set-up. The controllers offer multiple input & output EQ Filters, Routing, Peak Limiting, Compression Settings over a 96Hz sample rate

British Acoustics

Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com

www.britishacoustics.com

Delta Drive 28X

Digital standalone audio processing system

Technical Specifications

Audio Input	2 x Balanced XLR
Audio Output	8 x Balanced XLR
Minimum Load	150 Ohms
THD+N	0.0001% at 1kHz
Sound to Noise Ratio	>110dB
Frequency Response	>110dB
AD & DA Converters	20 Hz - 20 kHz
Parametric EQ	11 filters per input selected as Bell or Shelving 7 filters per output selected as Bell or Shelving
Centre Frequency	Selectable with a 1/24th of octave resolution step from 20Hz up to 20kHz Butterworth 6/12/18/24 dB per octave Bessel 12/24 dB per octave

General Specifications

Enclosure	Aluminium Extrusion
Finish	Metallic Finish
Optional Accessories	Flight Case
Colour	Black
Height	1.6"
Width	19"
Depth	9"
Weight	5 Kgs

