ALPHA BLU 412

12" BLU-SERIES PERFORMANCE INSTALLATION SPEAKER





ALPHA BLU 412 BLU SERIES INSTALLATION SPEAKER

The British Acoustics Alpha Blu 412 is a premium 12-inch performance installation speaker, delivering unmatched clarity and reliability. Designed for professional applications, it features a 2.5-inch copper voice coil LF driver and a 1.4-inch HF compression driver, ensuring exceptional sound reproduction across a wide frequency range. Built to endure rigorous usage, the Alpha Blu 412 is a trusted choice for both indoor and outdoor environments.



Crafted with a marine-grade birch plywood enclosure and coated in scratch-free polyurea paint, this speaker is as durable as it is visually appealing. The perforated black steel grills offer protection and a polished look. User-friendly features such as integrated handles, sloped input plates, and M10 flying inserts make installation and handling seamless. Its rotatable horns and compatibility with a range of installation brackets make the Alpha Blu 412 a flexible and dependable solution for modern sound systems.









ACOUSTICAL SPECIFICATIONS

- Freq. Response (-3 dB) : 59 Hz 20 kHz
- Freq. Range (-10 dB) : 50 Hz 20 kHz
- Rated Power : 500W AES, 2000W Peak
- H Dispersion : 90° (- 6 dB)
- V Dispersion : 50° (- 6 dB)
- User Rotatable Horns
- Crossover : 2.1 kHz or Bi-amplified
- Nominal Impedance : 8 Ω
- Max Output : Cont 127 dB, Peak 133 dB
- 2 x Speak-On Sockets, Input & Thru

SYSTEM SPECIFICATIONS

- Recommended Subwoofers : See Systems Chart for compatible subwoofers
- Recommended System Control : Delta Drive
 DSP Control Systems
- Recommended Amplifiers : See Amplifier load calculation chart

LF TRANSDUCER

- 12" Low Frequency Driver
- 450W AES, 1800W Peak
- 2.5" Copper Voice Coil Ferrite Magnet

- Enhanced Airflow Path for minimal power
- Aluminum Demodulation Ring for reduced distortion

HF TRANSDUCER

- 1.4" Exit HF Compression Driver
- 50W AES, 200W Peak
- 2.5" Voice Coil Ferrite Magnet
 Alpha Contour Waveguide ensuring consistent coverage

HOUSING

- Marine Birchply Enclosure
- Granular Scratch Free Polyurea Paint
- Perforated Black, Pressed Steel Grills
- Integrated Handles on Either Side
- Includes a set of round bottom feet for secure and stable stacking
- Sloped Input Plates
- M10 Flying inserts
- Installation brackets : Alpha Throne (H), Alpha Throne (V), Alpha Yoke B410

AESTHETIC SPECIFICATIONS

British Acoustics Signature Umber Brown

BA & British Accustics are registered trademarks in the UK and other regions worldwide Safe Installation & Rigging Practices - Installation must be by autorized personnel, following safety and rigging standards to avoid liability. "Product specifications and design may change due to raw material variations or the addition of new features and technologies for improved performance and reliability "5PL Calculated" (IIII, The Fried With Thirk Noise - Corest Factor 4



Tone

nos, minimum)

Blue Decals on Grills for better AestheticsAvailable in a RAL code of your choice (24

IP SPECIFICATIONS

• Standard Version : IP 42 - Offers basic protection against dust & splashes

OPERATING PARAMETERS

- Operating positions: Can be deployed horizontally or vertically with the correct installation brackets or can be used as a monitor
- Maximum permitted ambient temperature (Ta max) 55° C (124° F)
- Minimum permitted ambient temperature (Ta min): -20° C (-4° F)

OPTIONAL ACCESSORIES

• See system chart for the Systm Accessories

0

0

۲

SIZE

- Product: 622 x 355 x 457 mm (H x W x D)
- Product: 24 x 16 x 13 inch (H x W x D)
- Packed individually

WEIGHT

- Net : 21.7 Kgs
- Net : 47.8 Lbs

SHIPPING INFORMATION

- Carton Size
 697 x 430 x 532 mm (H x W x D)
 27.4 x 16.9 x 20.9 inch (H x W x D)
- Gross Weight : 22.7 Kgs / 50Lbs
- Packed : Individually

PRODUCT INFORMATION

- Model No : Alpha Blu 412
- Series 4
- Tags : 12" Blu-Series Performance Installation Speaker





One Basecamp, 49 Jamaica Street, Liverpool, L10AH, Great Britain. Email - info@britishacoustics.com | Tel - +44 (0) 151 515 0170 www.britishacoustics.com