

5 Series

XP Systems - Passive Portable PA Systems



Applications

- Portable sound reinforcement
- Stage Monitoring
- Corporate Events
- Mobile DJ & Touring
- Infill for large systems
- Educational Installations

Features

- Portable mid format Passive Speakers
- Compact and powerful performance
- High power low frequency transducer
- Coverage pattern of 10° x 60°
- High density polypropylene enclosure
- 8Ω nominal impedance

Products in the Series

- XP 515
- XP 512
- XP 510
- XP 508

The XP series provides contractors an economic yet effective option to fulfill PA requirements. The systems are built to be minimalistic and optimised for Classrooms, Presentation Centres, Seminar Halls and other such areas where speech intelligibility is paramount.

British Acoustics

Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com

www.britishacoustics.com

XP 508

2-Way, 1 x 8" Passive Loudspeaker

Technical Specifications

Frequency Response (-3 dB)	68 Hz - 20 kHz
Frequency Range (-10 dB)	55 Hz - 20 kHz
Coverage Pattern	100° x 60°
Max Spl	120 dB
Rated Power	150W Continuous, 600W Peak
LF Driver	Heavy Duty 8" LF Driver, 1.5" VC - Ferrite
HF Driver	1" exit compression driver, 1" VC
Sensitivity	94 dB
Nominal Impedance	8 ohms
Crossover Frequency	3.2 kHz

General Specifications

Enclosure	High-density polypropylene enclosure
Grill	Powder coated durable grill with acoustically Transparent foam
Finish	Sesimic Grey, Matte Paint Finish
Mounting System	6 fastening points (M8 type) for suspension, 35mm pole-mount adapter for stands and side-handle for transportation
Height	17"
Width	10"
Depth	9.8"
Weight	11 Kgs

