

9 Series

Monitoring - Co-axial, Elegant & Tour-ready Stage Monitors



Applications

- Stage Monitoring
- Multi-purpose Design for FOH use
- Theatre Sound Reinforcement
- High Energy Installations

Features

- Point-source phase coherent response
- Consistent 60 x 40 coverage
- Low-profile design for touring & broadcast applications
- High Acoustic Output (136 dB SPL)
- Suited for floor monitoring, FOH and side-fill applications
- Optional horizontal & vertical yokes

Products in the Series

- Delta 95X
- Delta 92X

The 9 series co-axial monitors are a range of high performance stage monitors, with a coherent response, low profile elegant aesthetics, and a rugged tour ready build. Our Twin-wave high-frequency waveguide ensures a smooth & consistent 60 x 40 coverage. The series comes pre-fitted with our low-noise crossovers for a plug & play 8 ohms use

British Acoustics

Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com

www.britishacoustics.com

Delta 95X

15" Co-axial Multipurpose Monitor

Technical Specifications

Frequency Range (-10 dB)	50Hz - 18 kHz
Frequency Response (-3 dB)	68Hz - 18kHz
Coverage Pattern	80° x 80°
Max Spl	133 dB
Crossover Frequency	1.2 kHz
Rated Power	400W AES, 1600W peak
Nominal Impedance	Passive: 8 ohms, Bi-amp LF: 8 ohms, Bi-amp HF: 8 ohms
LF Driver	15" Coaxial 2-Way High Power Driver, 3" VC - Ferrite
HF Driver	1.5" exit compression driver, 3" VC
Sensitivity	100 dB

General Specifications

Enclosure	Marine Birchwood Cabinet, Premium Grade
Grill	Powder coated durable grill with acoustically transparent foam
Finish	British Acoustics' Signature Brown Finish
Mounting System	Pole Mount Socket - Wood Recessed Handles - M-10 insertion points
Height	17"
Width	22.6"
Depth	15"
Weight	41.5 Kgs

